

Cold Rooms

Cold Rooms are constructed from modular puf panels. Each panel is interlocked securely to adjacent panels with the cam lock arrangement incorporating tongue & groove. Standard panels are finished in a white corrosion resistant pre coated sheet or PVC laminate film on galvanized steel panels. AISI 304 grade SS finish is also available as a standard. Cold Room panels are insulated with in-situ polyurethane foam injected using high pressure technology. Hinged doors can stay open at 120°. The doors are designed to be self-closing. Flooring is offered in Altro, tiling or kota stone. The cold rooms incorporate the latest technology and come with most efficient & calibrated refrigeration systems.



Model	Dimensions (mm) (wxdxh)	Temperature Range (°C)	Electrical Load (Kw)
Walk In Chillers			
WIC 2424	2400 X 2400 X 2550	2°C to 4°C	1.50
WIC 2427	2400 X 2700 X 2550	2°C to 4°C	1.50
WIC 2430	2400 X 3000 X 2550	2°C to 4°C	2.00
WIC 2433	2400 X 3300 X 2550	2°C to 4°C	2.00
WIC 2436	2400 X 3600 X 2550	2°C to 4°C	2.00
WIC 2736	2700 X 3600 X 2550	2°C to 4°C	2.00
WIC 2745	2700 X 4500 X 2550	2°C to 4°C	2.50
Walk In Freezers			
WIF 2424	2400 X 2400 X 2550	-22°C to -18°C	1.50
WIF 2427	2400 X 2700 X 2550	-22°C to -18°C	1.50
WIF 2430	2400 X 3000 X 2550	-22°C to -18°C	2.00
WIF 2433	2400 X 3300 X 2550	-22°C to -18°C	2.00
WIF 2436	2400 X 3600 X 2550	-22°C to -18°C	2.00
WIF 2736	2700 X 3600 X 2550	-22°C to -18°C	2.00
WIF 2745	2700 X 4500 X 2550	-22°C to -18°C	2.50

Sale / Registered Office: A-2, 2nd floor, Shopping Centre,
Naraina Industrial Area, Phase-II, New Delhi-110028
Ph.: +91-11-43157300, **Mob.:** 9810590040
Email: salesdesk@asterindia.com

aster
Food service equipment